



# Visual Cloud Accelerator Card - Analytics

Release Notes

---

*Rev. 3.0*

*November 2019*



You may not use or facilitate the use of this document in connection with any infringement or other legal analysis concerning Intel products described herein. You agree to grant Intel a non-exclusive, royalty-free license to any patent claim thereafter drafted which includes subject matter disclosed herein.

No license (express or implied, by estoppel or otherwise) to any intellectual property rights is granted by this document.

All information provided here is subject to change without notice. Contact your Intel representative to obtain the latest Intel product specifications and roadmaps.

The products described may contain design defects or errors known as errata which may cause the product to deviate from published specifications. Current characterized errata are available on request.

Copies of documents which have an order number and are referenced in this document may be obtained by calling 1-800-548-4725 or visit <http://www.intel.com/design/literature.htm>.

Intel technologies' features and benefits depend on system configuration and may require enabled hardware, software or service activation. Performance varies depending on system configuration. No computer system can be absolutely secure. Check with your system manufacturer or retailer or learn more at [intel.com](http://intel.com).

Intel, the Intel logo, and Atom, Core, and Xeon are trademarks of Intel Corporation or its subsidiaries in the U.S. and/or other countries.

\*Other names and brands may be claimed as the property of others.

Copyright © 2019, Intel Corporation. All rights reserved.



## Contents

---

<b>1.0 Introduction.....</b>	<b>5</b>
1.1 Supported Features.....	5
1.2 What's New.....	5
1.3 Supporting Documentation.....	6
<b>2.0 VCAC-A Release 3.0 Content.....</b>	<b>7</b>
<b>3.0 Fixed Issues.....</b>	<b>9</b>
<b>4.0 Known Issues.....</b>	<b>10</b>
<b>5.0 Acronyms and Terms.....</b>	<b>11</b>



## Revision History

---

Date	Revision	Description
November 2019	3.0	<a href="#">1.2 What's New</a> on page 5: Updated section to list new features for R3. <a href="#">2.0 VCAC-A Release 3.0 Content</a> on page 7: Updated for release R3.
September 2019	1.5	<a href="#">1.1 Supported Features</a> on page 5: Added JPEG acceleration. <a href="#">1.2 What's New</a> on page 5: Updated section to list new features. <a href="#">2.0 VCAC-A Release 3.0 Content</a> on page 7: Updated to include HOST and OpenVINO R2 details and package and file information. <a href="#">3.0 Fixed Issues</a> on page 9: Updated section to add issues fixed since the last release. <a href="#">4.0 Known Issues</a> on page 10: Updated issue IDs, added issues VMPI-570 and VCASS-2857, and moved issues VCASS-1771, VCASS-2576, VCASS-2563, VCASS-2577, VCASS-2564, VCASS-1552, and VCASS-1621 Fixed Issues. <a href="#">5.0 Acronyms and Terms</a> on page 11: Added HOST to Acronym list.
August 2019	1.1	<a href="#">4.0 Known Issues</a> on page 10: Added new items to Known Issues table.
July 2019	1.0	Initial document version.



## 1.0 Introduction

---

### NOTE

This document provides a brief introduction to the Visual Cloud Accelerator Card - Analytics, lists known and fixed issues, and provides available workarounds. In addition, a list of important acronyms and terminology is provided. The content of this document will be updated as applicable and updates will be reflected in the Revision History.

---

The Visual Cloud Accelerator Card - Analytics (VCAC-A) equips 2nd Generation Intel® Xeon® Scalable Processor based platforms with Iris® Pro Graphics and Intel Movidius VPU to enhance the video decoder, computer vision, and inference capabilities. Comprised of one Intel i3-7100U CPU and 12 Movidius VPU, this PCIe add-in card delivers competent stream inference capability and outstanding total cost of ownership. The applications focus on computer vision, video decode, and media analytics but is not limited to these items.

This release is a software package that includes OpenVINO, Intel Media Server Studio, FFmpeg, etc. The software package supports VCAC-A easy installation, friendly customization, and convenient deployment.

## 1.1 Supported Features

- Sample for implementation of Video Surveillance: Face/Car Detection on top of VCAC-A software stack.
- VCAC-A Service-to-VCAC-A agent workload dispatch through gRPC/Restful API.
- VCAC-A card driver and utility to control VCAC-A card.
- Inference Engine supported by OpenVINO.
- Hardware acceleration for h.264, h265, and JPEG decoder.

## 1.2 What's New

- Upgraded OpenVINO to 2019\_R3 release (l\_openvino\_toolkit\_p\_2019.3.334.tgz).

### NOTE

HOST and VCAA agent mentioned below are available in IPS, please contact your Intel® representative for access.

---

- Enabled HOST pipelines of three use cases (emotion recognition, crowd counting and pedestrian detection).



- Refined VCAA agent feasibility to download pipeline configuration files through gRPC.
- Enhanced HOST robustness for multi-network/multi-density/multi-thread use.

### **1.3 Supporting Documentation**

Please see the following documents for more information on the Analytics card:

- *Visual Cloud Accelerator Card - Analytics Software Installation Guide, Doc# 611894*
- <https://hardwaresupport.celestica.com> (please contact your Celestica™ representative for access)



## 2.0 VCAC-A Release 3.0 Content

The package delivered with this release includes the following folder structure.

The package delivered with this release includes the following folder structure. Download the release content from the following link: [https://github.com/OpenVisualCloud/VCAC-SW/archive/VCAC-A\\_R3.tar.gz](https://github.com/OpenVisualCloud/VCAC-SW/archive/VCAC-A_R3.tar.gz).

**Table 1. Release Package Folder Structure**

Ingredient	Path	Contents
VCAC-A Host Files	Intel_Media_Analytics_Host/scripts	build.sh Dockerfile
	Intel_Media_Analytics_Host/tar/	centos7.4-kernel3.10.0-patch.tar.gz
	Intel_Media_Analytics_Host/tar/	vcass-modules-3.10.0-patch.tar.gz
VCAC-A Software Installation Packages	Intel_Media_Analytics_Node/scripts/	vcad_build.sh Dockerfile
	Intel_Media_Analytics_Node/tar/	ubuntu16.04_kernel4.19_patch.tar.gz
	Intel_Media_Analytics_Node/tar/	vcass-modules-4.19-patch.tar.gz

The following bullets provide a list detailed components included in the package.

- VCAC-A Host files consist of:
  - Scripts to build kernel and VCAC-A PCIE driver modules.
  - Dockerfile for creating the docker container of CentOS 7.4, called by the script to build kernel and driver modules.
  - VCAC-A host support package:
    - kernel patch
    - VCAC-A PCIE driver patch
- VCAC-A software installation package contains the following components:
  - Script to build the system image to be loaded on VCAC-A card.
  - Dockerfile for creating the docker container of Ubuntu 16.04, called by the script to build the system image to be loaded on VCAC-A.
  - VCAC-A card support package:
    - kernel patch
    - driver module patch

Refer to the *VCAC-Analytics Software Installation Guide*, Doc# 611894 for information on how to setup the environment with the release packages.



Media Analytics end-to-end pipeline construction solution package is available in IPS. Please contact your Intel® representative for access to the package.

**Table 2. Solution Packages in IPS**

Ingredient	Path	Contents
Heterogeneous Optimized Scheduling Tool (HOST)	Intel_Media_Analytics_Node/deb/	intel-vcaa-ddwo-ubuntu16.04-amd64.deb
VCAA Agent	Intel_Media_Analytics_Node/vcaa_agent/	vcaa_agent.tar.gz

The following bullets provide the description of the contents:

- **Heterogeneous Optimized Scheduling Tool (HOST):** is an optimization tool to build efficient and flexible pipelines for a variety of workloads (such as decoding, inferencing, etc) based on API/SDKs (MSDK, OpenVINO). It provides a heterogeneous scheduler to deploy routines in tasks to different hardware components (GPU/CPU/VPU).
- **VCAA Agent:** Daemon service in VCAC-A card.





## 3.0 Fixed Issues

The following table details issues fixed previously.

**Table 3. Fixed Issues**

Issue ID	Exposure	Title & Workaround
VCASS-2576	Medium	vcactl get-BIOS-cfg command does not work for card. <b>Workaround:</b> N/A
VCASS-2563	Medium	vcactl config-default command does not work on only one analytics card in the server (cannot restore default configuration). <b>Workaround:</b> N/A
VCASS-2577	Low	vca_elog.py script failed with CLS BIOS. <b>Workaround:</b> N/A
VCASS-2564	Low	Bash completion does not work on CentOS system. <b>Workaround:</b> N/A
VCASS-1552	Low	User can set different characters in config auto-boot. <b>Workaround:</b> N/A
VCASS-1621	Low	Can set a mask with character, i.e. "abcd" (instead of numeric value). <b>Workaround:</b> N/A



## 4.0 Known Issues

The following table details currently known issues effecting the accelerator card.

**Table 4. Known Issues**

Issue ID	Exposure	Title & Workaround
VCASS-2857	High	Node 0 and Node 1 can cause interference (cause a DMA hang) with each other. This situation can happen when one node is using network (between host & card) traffic and another one is rebooted or reset at the same time. <b>Workaround:</b> Reboot host server to recover from DMA hang.
VCASS-2578	High	VCA config file is broken after non-graceful system shutdown (power switch restarts). <b>Workaround:</b> Execute <code>vcactl config-default</code> command.
VCASS-152	Low	Confusing message in <code>vca_config_upgrade.sh</code> script. <b>Workaround:</b> N/A
VCASS-27	Low	<code>vca_config_upgrade.sh</code> script does not recover removed option in manual mode. <b>Workaround:</b> N/A
VMPI-41	Medium	Switching Plugin from HDDL to MYRAID shows error. OpenVINO design does not support switching between the <code>hddldaemon</code> and <code>Myraid X</code> plugins. A user must run <code>bsl_reset</code> and reboot to switch between the plugins. <b>Workaround:</b> Commands to recover that are shared by OpenVINO are: <code>kill -9 \$(pidof hddldaemon autoboot) pidof hddldaemon autoboot</code> . Ensure that none of the commands are alive source <code>/opt/intel/opencvino/bin/setupvars.sh \${HDDL_INSTALL_DIR}/bin/bsl_reset</code> .
VMPI-139	Medium	<code>vgg16</code> could not run with density 24 due to a VCAC-A DDR memory size limitation. 24 x <code>vgg16</code> density workloads cannot be run simultaneously on a VCAC-A card. <b>Workaround:</b> N/A
VMPI-570	Medium	Intel® model <code>vehicle-license-plate-detection-barrier-0106</code> does not support dynamic batch size. Running OpenVINO sample <code>benchmark_app</code> to do inference with this model by setting batch size with the <code>-b</code> parameter will fail. <b>Workaround:</b> N/A



## 5.0 Acronyms and Terms

---

The following acronyms and terms are used in this document.

Acronym/Term	Description
FFMPEG	A popular media framework
HOST	Heterogeneous Optimized Scheduling Tool
IE	Inference Engine
Intel® MSS	Intel® Media Server Studio
MSDK	Media Software Development Kit
KMD	Kernel Mode Driver
OpenCL	Open Computing Language
OpenVINO	Open Visual Inference & Neural network Optimization
Scheduler	Load balance package
UMD	User Mode Driver
VCAC-A	Visual Cloud Accelerator Card - Analytics
VPU	Visual Process Unit